



- PROVIDES POSITIVE, POWERFUL TILTING - 45deg IN EITHER DIRECTION FOR SLOPE GRADING, DITCH CLEANING, SHAVING TRENCH EDGES, etc.
- THE "MAIN PIVOT" IS THE HEART OF ANY HYDRAULIC TILTING BUCKET. OUR UNIQUE DESIGN FEATURES HEAT TREATED MAIN PIVOT PIN WITH ADJUSTABLE LOCK-NUT, BUSHINGS, SEALS AND THRUST BEARINGS WHICH WILL OFFER LONG, TROUBLE FREE SERVICE LIFE.
- HEAT TREATED 400BHN BASE EDGE IS DRILLED AND COUNTERBORED TO PROTECT NUTS FROM WEAR AND CREATE A SMOOTH INSIDE PROFILE. ONE PIECE OR THREE PIECE REVERSIBLE B/O EDGE INCLUDED.
- HEAT TREATED 400BHN SIDE LEADING EDGES AND VERTICAL AND HORIZONTAL WEAR STRIPS
- HEAVY DUTY HYDRAULIC CYLINDERS HAVE INDUCTION HARDENED RODS, PINS, & BUSHINGS.
- HYDRAULIC HOSES ARE NEATLY ROUTED TO BUCKET EARS AND PROTECTED AGAINST DAMAGE BY GUARDING AND PARTEX SLEEVE
- AUXILIARY HYDRAULIC KITS AVAILABLE FOR USE WITH BUCKET.
- MANUFACTURED IN VIRGINIA, USA & SCOTLAND, UK



MODEL	WIDTH		CAPACITY		MACHINE SIZE	
	INCH	MILLIMETER	YARD 3	METER 3	POUND	KILOGRAM
HT12	46 = 84	1,168 = 2,134	0.635 = 1.200	0.581 = 1.097	24,500 = 30,500	11,113 = 13,835
HT15	46 = 72	1,168 = 1,829	0.716 = 1.154	0.655 = 1.055	30,500 = 40,000	13,835 = 18,144
HT18	48 = 72	1,219 = 1,829	0.837 = 1.292	0.765 = 1.181	??? = ???	??? = ???
HT21	48 = 84	1,219 = 2,134	0.933 = 1.697	0.853 = 1.552	40,000 = 50,000	18,144 = 22,680
HT25	48 = 84	1,219 = 2,134	1.099 = 2.002	1.005 = 1.831	50,000 = 58,000	22,680 = 26,308
HT30	48 = 102	1,219 = 2,591	1.293 = 2.902	1.182 = 2.654	58,000 = 68,000	26,308 = 30,844
HT40	48 = 96	1,219 = 2,438	1.699 = 3.609	1.554 = 3.300	??? = ???	??? = ???



LEMAG
ENGINEERING

UK / EUROPE

Email: uksales@lemaonline.com
Phone: +44 (0) 1259-751573

Website: www.LemaOnline.com

LEMAG
CORPORATION

US / CANADA

Email: sales@lemaonline.com
Phone: 1 (804) 862-8481

Distributed By:

(Attach Business Card Here)