



- ❏ **QUENCHED & TEMPERED ALLOY STEEL 130,000 psi MIN. YIELD, 360 - 440 BHN IS USED IN CUTTING EDGE, RIBS, OUTER RIB WEAR STRIP.**
- ❏ **WHILE OFTEN COPIED BUT NEVER DUPLICATED, THE LEMAC HEAVY TUBE SECTION DESIGN FORMS THE TOP BEAM OF THE BUCKET PROVIDING AN EXTREMELY SOLID BASE FOR THE MOUNTING EARS. CORNER GUSSETS INSURE RIGIDITY IS MAINTAINED FOR LONG BUCKET LIFE**
- ❏ **CUSTOM RIB SPACING FOR PERFECT APPLICATION**
- ❏ **AGGRESSIVELY SHAPED TO PROMOTE EASY PENETRATION FOR QUICK SIFTING**
- ❏ **OPTIONAL LOWER SIDECUTTERS AVAILABLE**
- ❏ **OFFERED WITH A WIDE VARIETY OF TOOTH SYSTEMS INCLUDING CAT STYLE, HENSLEY, & ESCO ETC.**
- ❏ **OPTIONAL DRAINAGE HOLES AVAILABLE**
- ❏ **SUITABLE FOR MINI'S TO HEAVY EXCAVATORS**
- ❏ **CUSTOM ORDER WITH BOLT-ON EDGES INSTEAD OF STANDARD TOOTH ASSEMBLIES**
- ❏ **ONE YEAR OR 1,500 HOUR WARRANTY**
- ❏ **MANUFACTURED IN VIRGINIA, USA & SCOTLAND, UK**



MODEL	WIDTH		CAPACITY		MACHINE SIZE	
	INCH	MILLIMETER	YARD 3	METER 3	POUND	KILOGRAM
SK 12	46 = 84	1,168 = 2,134	0.635 = 1.200	0.581 = 1.097	24,500 = 30,500	11,113 = 13,835
SK 15	46 = 72	1,168 = 1,829	0.716 = 1.154	0.655 = 1.055	30,500 = 40,000	13,835 = 18,144
SK 18	48 = 72	1,219 = 1,829	0.837 = 1.292	0.765 = 1.181	??? = ???	??? = ???
SK 21	48 = 84	1,219 = 2,134	0.933 = 1.697	0.853 = 1.552	40,000 = 50,000	18,144 = 22,680
SK 25	48 = 84	1,219 = 2,134	1.099 = 2.002	1.005 = 1.831	50,000 = 58,000	22,680 = 26,308
SK 30	48 = 102	1,219 = 2,591	1.293 = 2.902	1.182 = 2.654	68,000 = 85,000	30,844 = 38,555
SK 40	48 = 96	1,219 = 2,438	1.699 = 3.609	1.554 = 3.300	85,000 = 104,000	38,555 = 47,174



LEMAC
ENGINEERING

UK / EUROPE

Email: uksales@lemaconline.com
Phone: +44 (0) 1259-751573

Website: www.Lemaconline.com

LEMAC
CORPORATION

US / CANADA

Email: sales@lemaconline.com
Phone: 1 (804) 862-8481

Distributed By:

(Attach Business Card Here)